

ConTeXt 2023.09.04 19:15

```
node=emptynode:  
ifxmlselfempty-else-fi: attribute = !empty node!  
ifxmlselfempty-else-fi reversed: content =  
  
node=notemptynode:  
ifxmlselfempty-else-fi: content = !not empty node!  
ifxmlselfempty-else-fi reversed: attribute =  
  
\startxmlsetups xml:emptynode  
node=\xmltag{#1}:\crlf  
ifxmlselfempty-else-fi:\space  
\ifxmlselfempty{#1}  
    attribute = \xmlatt{#1}{value}  
\else  
    content = \xmlflush{#1}  
\fi  
\crlf  
ifxmlselfempty-else-fi reversed:\space  
\ifxmlselfempty{#1}  
    content = \xmlflush{#1}  
\else  
    attribute = \xmlatt{#1}{value}  
\fi  
\blank  
\stopxmlsetups  
  
\startxmlsetups xml:notemptynode  
node=\xmltag{#1}:\crlf  
ifxmlselfempty-else-fi:\space  
\ifxmlselfempty{#1}  
    attribute = \xmlatt{#1}{value}  
\else  
    content = \xmlflush{#1}  
\fi  
\crlf  
ifxmlselfempty-else-fi reversed:\space  
\ifxmlselfempty{#1}  
    content = \xmlflush{#1}  
\else  
    attribute = \xmlatt{#1}{value}
```

```
\fi  
\blank  
\stopxmlsetups
```